

**TECHNICAL SPECIFICATION****Model : AE 1327Y****BOM ID : 325****Low Torque Start**

Electrical: 220-240 Volt	50 Hz	1 Phase
---------------------------------	--------------	----------------

Nominal Performance:

Cooling Capacity	67.00/0.00 Watts
	228.60/0.00 BTU/Hr
	57.61/0.00 Kcal/Hr
Power Input	75.00/0.00 Watts
Lock Rotor Amps	5.30 Amps
Rated Load Amps	0.56 Amps
COP	0.89/0.00 Watts / Watts

Testing Conditions:

Condensing Temperature	54.4 C
Evaporating Temperature	-23.3 C
Liquid Temperature	32.2 C
Return Gas Temperature	32.2 C
Ambient Temperature	32.2 C

Application:

Evaporating Range	LBP	@-34.4 C to-12.2 C
	Heat Pump - C to- C	
Refrigerant	R134a	
Expansion	Capillary Tube	
Compressor	Natural Convection	

Compressor and Motor data:

Compression Type	Reciprocating
Displacement	3.90 cc.
Oil Type	Polyolester Oil
Oil Charge	296 cc.
Motor Type	R.S.I.R.; 2 Pole 2880 - r/m
Voltage Range	187 - 264 cc.
Winding Resistance at 25 C	
Start	59.04 Ohms
Run	22.03 Ohms
Weight with Oil	8.60 Kg.
Weight with Oil and Accessories	8.78 Kg.

Electrical Components:**Motor Protector**

Type	External 5TM
Model	KME 670-20
Open / Close	100-110/70-52 C
1st Cycle trip at 25 C	5.2 Amps(start) - Amps(start)

Motor Starter

Type	Current Relay
Model Number	KME 690-20
Pick Up (max.)	-
Drop Out (min.)	-
Terminal Cover	KMD 902-2
Start Capacitor	No F No VAC
Run Capacitor	No F No VAC
Disch. Resistor	No

Mounting Kit

Rubber Gromment:	KMD 905-3	Earth Plug:	-
Sleeve Gromment:	KMD 903-2	Earth Screw:	-
Washer:	KEB 387	Washer Lock:	-

Certificate Marks: