

**TECHNICAL SPECIFICATION****Model : AE 1327Y-2****BOM ID : 326****Low Torque Start**

<b>Electrical: 208-230 Volt</b>	<b>60 Hz</b>	<b>1 Phase</b>
---------------------------------	--------------	----------------

**Nominal Performance:**

Cooling Capacity	81.00/0.00 Watts
	276.37/0.00 BTU/Hr
	69.65/0.00 Kcal/Hr
Power Input	88.00/0.00 Watts
Lock Rotor Amps	7.30 Amps
Rated Load Amps	0.70 Amps
COP	0.92/0.00 Watts / Watts

**Testing Conditions:**

Condensing Temperature	54.4 C
Evaporating Temperature	-23.3 C
Liquid Temperature	32.2 C
Return Gas Temperature	32.2 C
Ambient Temperature	32.2 C

**Application:**

Evaporating Range	LBP	@-34.4 C to- 12.2 C
	Heat Pump - C to- C	
Refrigerant	R134a	
Expansion	Capillary Tube	
Compressor	Natural Convection	

**Compressor and Motor data:**

Compression Type	Reciprocating
Displacement	3.90 cc.
Oil Type	Polyolester Oil
Oil Charge	296 cc.
Motor Type	R.S.I.R.; 2 Pole 3500 - r/m
Voltage Range	187 - 264 cc.
Winding Resistance at 25 C	
Start	59.60 Ohms
Run	15.65 Ohms
Weight with Oil	8.71 Kg.
Weight with Oil and Accessories	8.86 Kg.

**Electrical Components:**

<b>Motor Protector</b>	
Type	External 3/4"
Model	KME 660-33/C
Open / Close	100-110/70-52 C
1st Cycle trip at 25 C	3.5 Amps(start) - Amps(start)

**Motor Starter**

Type	Current Relay
Model Number	KME 681-13
Pick Up (max.)	2.2
Drop Out (min.)	1.95
Terminal Cover	KMD 901-5
Start Capacitor	No F No VAC
Run Capacitor	No F No VAC
Disch. Resistor	No

**Mounting Kit**

<b>Rubber Gromment:</b>	KMD 905-3	<b>Earth Plug:</b>	-
<b>Sleeve Gromment:</b>	KMD 903-2	<b>Earth Screw:</b>	-
<b>Washer:</b>	KEB 387	<b>Washer Lock:</b>	-

**Certificate Marks:****RoHS**