

**TECHNICAL SPECIFICATION****Model : AE 1335YK-K****BOM ID : 306****Low Torque Start**

Electrical: 220-240 Volt		50 Hz	1 Phase
Nominal Performance:			
Cooling Capacity	93.00/0.00 Watts		
	317.32/0.00 BTU/Hr		
	79.97/0.00 Kcal/Hr		
Power Input	94.00/0.00 Watts		
Lock Rotor Amps	6.10 Amps		
Rated Load Amps	0.76 Amps		
COP	0.99/0.00 Watts / Watts		
Testing Conditions:			
Condensing Temperature	54.4 C		
Evaporating Temperature	-23.3 C		
Liquid Temperature	32.2 C		
Return Gas Temperature	32.2 C		
Ambient Temperature	32.2 C		
Application:			
Evaporating Range	LBP	@-34.4 C to-12.2 C	
	Heat Pump - C to- C		
Refrigerant	R134a		
Expansion	Capillary Tube		
Compressor	Natural Convection		
Compressor and Motor data:			
Compression Type	Reciprocating		
Displacement	4.60 cc.		
Oil Type	Polyolester Oil		
Oil Charge	296 cc.		
Motor Type	R.S.I.R.; 2 Pole 2880 - r/m		
Voltage Range	187 - 264 cc.		
Winding Resistance at 25 C			
Start	39.57 Ohms		
Run	17.19 Ohms		
Weight with Oil	8.62 Kg.		
Weight with Oil and Accessories	8.76 Kg.		
Electrical Components:			
Motor Protector			
Type	External 3/4"		
Model	KME 660-2/CD		
Open / Close	90-100/70-52 C		
1st Cycle trip at 25 C	5.4 Amps(start) - Amps(start)		
Motor Starter			
Type	Current Relay		
Model Number	KME 681-18		
Pick Up (max.)	2.85		
Drop Out (min.)	2.5		
Terminal Cover	KMD 901-5		
Start Capacitor	No F No VAC		
Run Capacitor	No F No VAC		
Disch. Resistor	No		
Mounting Kit			
Rubber Gromment:	KMD 905-3	Earth Plug:	-
Sleeve Gromment:	KMD 903-2	Earth Screw:	-
Washer:	KEB 387	Washer Lock:	-

Certificate Marks:**RoHS**

TIS.812-2548