

**TECHNICAL SPECIFICATION****Model : AE 1360Y-1****BOM ID : 479****Low Torque Start**

Electrical: 115 Volt		60 Hz	1 Phase
Nominal Performance:			
Cooling Capacity	189.00/0.00 Watts		
	644.87/0.00 BTU/Hr		
	162.52/0.00 Kcal/Hr		
Power Input	170.00/0.00 Watts		
Lock Rotor Amps	21.80 Amps		
Rated Load Amps	2.35 Amps		
COP	1.11/0.00 Watts / Watts		
Testing Conditions:			
Condensing Temperature	54.4 C		
Evaporating Temperature	-23.3 C		
Liquid Temperature	32.2 C		
Return Gas Temperature	32.2 C		
Ambient Temperature	32.2 C		
Application:			
Evaporating Range	LBP	@-34.4 C to-12.2 C	
	Heat Pump - C to- C		
Refrigerant	R134a		
Expansion	Capillary Tube		
Compressor	Natural Convection		
Compressor and Motor data:			
Compression Type	Reciprocating		
Displacement	6.91 cc.		
Oil Type	Polyolester Oil		
Oil Charge	485 cc.		
Motor Type	R.S.I.R.; 2 Pole 3500 - r/m		
Voltage Range	98-132 cc.		
Winding Resistance at 25 C			
Start	7.34 Ohms		
Run	2.15 Ohms		
Weight with Oil	9.74 Kg.		
Weight with Oil and Accessories	9.89 Kg.		
Electrical Components:			
Motor Protector			
Type	External 3/4"		
Model	KME 664-6/C		
Open / Close	100-110/78-60 C		
1st Cycle trip at 25 C	13.5 Amps(start) - Amps(start)		
Motor Starter			
Type	Current Relay		
Model Number	kme 681-31		
Pick Up (max.)	8.8		
Drop Out (min.)	7.8		
Terminal Cover	KMD 901-5		
Start Capacitor	No F No VAC		
Run Capacitor	No F No VAC		
Disch. Resistor	No		
Mounting Kit			
Rubber Gromment:	KMD 905-3	Earth Plug:	-
Sleeve Gromment:	KMD 903-2	Earth Screw:	-
Washer:	KEB 387	Washer Lock:	-

Certificate Marks:**RoHS**