

CAE / CWJ / CAW Condensing Units

Low/Medium/High Temperature Application - Capacity (Watts)

MODEL NUMBER	Application	Refrig.	HP	Unit Power	RLA	Displ.	Volt.	Connections(in.)		Dimensions (mm.)			Net weight Kg	Motor Type	EVAPORATING TEMPERATURE °C											
								Suction	Liquid	Depth	Width	Hight			-40	-35	-30	-25	-20	-15	-10	-5	0	5	10	
CAE7415EB	M	R22/R407C	1/4	480	2.8	5.48	220-240	3/8	1/4	330	470	302	17	CSIR							270	340	415	500	595	695
CAE7422EB	M	R22/R407C	1/4	470	2.8	7.55	220-240	3/8	1/4	330	470	302	17	CSIR							405	490	590	710	840	
CAE7426EB	M	R22/R407C	1/3	560	3.2	8.85	220-240	3/8	1/4	330	470	302	21	CSIR							500	610	740	875	1,020	
CAE7435EB	M	R22/R407C	3/8	580	2.8	12.01	220-240	3/8	1/4	330	470	302	22	CSR							620	780	945	1,120	1,310	
CAE7440EB	M	R22/R407C	1/2	750	3.4	14.14	220-240	3/8	1/4	330	470	302	23	CSR							745	925	1,120	1,325	1,545	
CAE7445EB	M	R22/R407C	3/4	850	3.0	16.08	220-240	3/8	1/4	330	470	302	22	CSR							930	1,160	1,390	1,655	1,960	
CAE7415YB	L/M	R134a	1/6	220	1.6	5.51	220-240	3/8	1/4	330	470	302	15	RSIR			75	100	125	160	200	250	305	380		
CAE7423YB	L/M	R134a	1/3	410	2.9	12.01	220-240	3/8	1/4	330	470	302	19	CSIR			175	235	310	400	500	610	745	890		
CAE7426YB	L/M	R134a	1/3	535	4.0	14.14	220-240	3/8	1/4	330	470	302	21	CSIR			200	270	350	455	570	700	850	1,030		
CAE7430YB	L/M	R134a	3/8	640	3.0	16.16	220-240	3/8	1/4	330	470	302	22	CSR			275	370	495	635	805	990	1,210	1,450		
CWJ2435ZB	LBP	R404A	3/4	830	3.3	21.50	220-240	1/2	3/8	435	550	337	37	CSR	360	510	710	930	1,170	1,430	1,710					
CWJ2450ZB	LBP	R404A	7/8	970	4.8	26.75	220-240	1/2	3/8	435	550	337	37	CSR	440	640	880	1,150	1,460	1,780	2,120					
CWJ2455ZB	LBP	R404A	1	1,060	5.5	30.50	220-240	5/8	3/8	435	550	337	37	CSR	490	740	1,000	1,270	1,580	1,910	2,290					
CWJ9460GB	MBP/HBP	R22/R407C	3/4	897	4.9	19.80	220-240	1/2	3/8	520	620	395	33	CSR							1,069	1,367	1,729	2,168	2,668	3,138
CWJ9470GB	MBP/HBP	R22/R407C	7/8	1,390	5.6	21.55	220-240	1/2	3/8	520	620	395	44	CSR							1,440	1,770	2,130	2,530	2,960	3,440
CWJ9485GB	MBP/HBP	R22/R407C	1	1,650	7.0	26.70	220-240	1/2	3/8	520	620	395	44	CSR							1,830	2,240	2,700	3,210	3,730	4,270
CAW2462ZB	LBP	R404A	1	1,120	4.7	39.60	220-240	5/8	3/8	550	860	346	53	CSR	535	805	1,080	1,370	1,665	1,970	2,280					
CAW2464ZB	LBP	R404A	1-1/4	1,380	5.8	43.10	220-240	5/8	3/8	550	860	421	53	CSR	795	1,115	1,475	1,865	2,290	2,775						
CAW2495ZB	LBP	R404A	1-1/2	1,800	7.8	53.50	220-240	5/8	3/8	550	860	421	67	CSR	920	1,280	1,710	2,190	2,720	3,350						
CAW4520GB	MBP/HBP	R22/R407C	1-1/2	1,660	7.9	37.50	220-240	5/8	3/8	550	860	346	61	CSR							2,170	2,650	3,190	3,790	4,440	
CAW4524GB	MBP/HBP	R22/R407C	2	2,150	9.6	43.10	220-240	5/8	3/8	550	860	346	69	CSR							2,400	3,050	3,760	4,550	5,340	6,280
CAW4528GB	MBP/HBP	R22/R407C	2-1/4	2,400	11.2	48.40	220-240	5/8	3/8	550	860	346	69	CSR							2,650	3,350	4,130	5,010	5,960	6,890
CAW4532GB	MBP/HBP	R22/R407C	2-1/2	2,550	12.5	53.50	220-240	5/8	3/8	550	860	346	74	CSR							2,930	3,760	4,580	5,490	6,490	